



Technical Data Sheet

QLE 1035

*Quantum Silicones' 38 Durometer Addition Cure
Elastomer for Coating Applications*

Product Description

QLE 1035 is a 100% silicone solids elastomer designed for fabric or cloth coating applications. This two component system offers a tough coating, excellent adhesion and fast cure.

Key Features

- 100% solids – no solvents
- Long pot life
- Excellent adhesion
- Tough, resilient coating

Typical Properties

Uncatalyzed Properties

	“A” Component	“B” Component
Viscosity, cps	18,000	800
Appearance	White	Clear
Specific Gravity, g/cm ³	1.34	0.98
Mix Ratio	100:10	

Catalyzed Properties (cured 20 min. @ 150C)

Pot life, hours	>24
Durometer, Shore A	38
Tensile, psi	200
Elongation, %	200

Mixing

Thoroughly stir both A and B components prior to mixing together.

Mixing by hand

Combine 100 parts of A component and 10 parts of B component by weight and stir until completely mixed. Use care when mixing to minimize air entrapment.

Mixing and dispensing with automatic equipment

Use properly ratioed equipment for a 100:10 mix ratio. Also use a mixing system that will properly mix A and B components. Once mixed properly the material will have >24 hour pot life.

Storage and Shelf Life

QLE 1035 should be stored in the original unopened container at 25C (77F). It will remain useful for a period of 12 months if stored under those conditions.

Not for Product Specification

The technical data listed herein are provided as a reference only and are not intended as sales specifications. For sales and technical assistance or for product recommendations, please call 1-800-852-3147.

Quantum Silicones
8021 Reycan Rd
Richmond, VA 23237
Phone (804) 271-9010 Fax (804) 271-9055
Customer Service (800)852-3147
www.quantumsilicones.com